



Verona Vertical Chrome

| Height mm | Length mm | Henrad Code | Heat emissions | |
|--------------|--------------|----------------|----------------|--------|
| | | | Watts | Btu/hr |
| 1800 | 310 | 751101 | 395 | 1348 |
| | 390 | 751102 | 495 | 1688 |
| | 470 | 751103 | 528 | 1801 |
| | 604 | 751104 | 654 | 2232 |

Btu/hr @ $\Delta t 50^{\circ}\text{C}$

Working pressure:
Tested to withstand 4.0 bar



For technical and installation
information visit our website
www.henrad.co.uk/downloads



Technical information

Testing and Operating Pressures

Henrad Verona Vertical Chrome has been independently tested to ensure these radiators perform to a maximum working pressure of 4.0 bar.

Finish

Chrome.

Water Treatment

Installation of the system should be properly flushed and fitted in accordance with the British Code of Practice for the Treatment of Water in Domestic Hot Water Central Heating Systems.

Warranty

Henrad Verona Vertical Chrome comes with a 5 year manufacturer's warranty.

Henrad Verona Vertical Chrome

Wall Mounting Information

All dimensions in mm.

| Type | Vertical | |
|---|----------|------|
| Height | 1800 | 2000 |
| Heated surface area (m ² /m) | 4.01 | 4.42 |
| Weight (kg/m) | 44.2 | 49.4 |
| Water contents (l/m) | 14.3 | 16.9 |
| Wall to tap centre (mm) | 43 | 43 |

| Width (mm) | X (mm) | Y (mm) |
|------------|--------|--------|
| 310 | 80 | 1590 |
| 390 | 160 | 1590 |
| 470 | 240 | 1590 |
| 604 | 356 | 1590 |

