

Technical Data NEW Compact Vertical





Technical Data NEW Compact Vertical

Technical Data

Testing and Operating Pressures

Henrad Compact Vertical has been independently tested to ensure radiators perform to a maximum working pressure of 10.0 bar.

Connections

Henrad Compact Vertical has $4 \ge 1/2''$ BSP connections as standard.

Paint Process

Two coat paint process, each Henrad radiator is subjected to a multi-stage cleaning and paint process.

The final powder coat is Traffic white (RAL A9016) which is stoved and cooled to give a perfect finish. All radiators are illustrated in Traffic white unless stated.

Water Treatment

Installation of the system should be properly flushed and fitted in accordance with the British Code of Practice for the Treatment of Water in Domestic Hot Water Central Heating Systems.


Warranty

Henrad Compact Vertical comes with a 10 year manufacturer's warranty.

Compact Vertical

Wall Mounting Information

All dimensions in mm. Inches in brackets.




Connections Each radiator comes with $1/2^{\prime\prime}$ inlet connections as standard.

Mounting Bracket Information


All dimensio	ons in mm.		
Height	H2	H3	H4
1600	70	740	1410
1800	70	840	1610
2000	70	940	1810
2200	70	1040	2010



Piping Options



Pressure Drops



Henrad (UK) Limited, Marriott Road, Mexborough, South Yorkshire S64 8BN. Telephone: 0800 876 6813